

## Overview

Organic solvent based graffiti remover for use on hard, painted surfaces, glass and plexiglass

## Product Description

Heavy duty organic solvent based product for the removal of graffiti from a variety of hard surfaces and soft. Ideal solution for removing aerosol graffiti, crayon, felt tips, inks and paint from most hard and soft surfaces.

Most hard surfaces except rubber/latex (take care with polycarbonates and laminates)

Vehicle paint (road and rail transport) as well as bare metal, glass (inc. windscreens), ceramic tiles and melamine.

Also suitable for use on stonework, brick, concrete, paving slabs and other porous surfaces.

Also suitable for some carpets, curtains, clothing, fabrics and upholstery.

*For more stubborn and hard to remove deposits such as chewing gum, consider the use of Rumexo Gum Solve*

## Features and Benefits

Features	Benefits
Suitable for most hard and soft surfaces	Powerful, fast acting formulations
Will remove a variety of oil based stains	Low Odour, no choking fumes
Does not contain acids or caustic	Compatible with most hard and soft surfaces
Does not contain chlorofluorocarbons	Manufactured in accordance with recognised international standards, ISO 9001

## Application/Directions for Use

Graffiti Remover is a ready to use product

Spray or brush onto the affected surface. Leave to work for a 2-20 minutes dependent upon the surface and soil type. Scrape off loosened or excess soil and wipe off or wash off with water. Repeat as necessary.

## Product Data Sheet Graffiti Remover

Porous surfaces may require several applications but in this case product can be left in contact with the soil for 2-8 hours before removal.

Ensure product is fully removed after treatment to prevent any long term discolouration

### Target Compounds:

Oil and water based paints, spray paint (cellulose, acrylic or polyurethane), Permanent Marker, Ball point Pen Ink (non-permanent dye), Crayon, Blue Tack, Contact Adhesives (cellotape remnants), Glue Deposits, Lipstick

**Disclaimer:** Solvent sensitive surfaces will be softened or dissolved by this product i.e. paints, some plastics, some fabrics. If graffiti is being removed from paintwork, soft plastics or delicate fabric, test on a small discrete area before general application. Do not use on varnished surfaces. **Product is for professional use only**

### STORAGE AND HANDLING

Store in a cool, dry place.

Keep the container tightly closed. DO NOT store or use near naked flames, sources of ignition or near heat sources.

Wash hands with soap and water after use.

### Packaging

12x500ml bottle/case

10L jerry cans



Rumexo Ltd  
Unit 11, Empire Business Park  
Parcel Terrace  
Derby  
DE1 1LY  
UK  
T: +44 (0)1283 221 297  
e: enquiries@rumexo.com

*The information provided in this Technical Data Sheet is accurate at the date of issue and should be used for indicative purposes only. Please refer to your Company Representative for specific User instructions as to how these relate to your usage requirements. Please note that Rumexo Ltd is not liable for claims, damages, costs or expenses of any kind arising from the mishandling of the product or changes that might occur during the handling, storage and application conditions provided by any third party who does not follow the minimum requirements defined in the SDS. Please refer to the SDS for further information regarding the handling, storage and*