

CHILLGUARD

OVERVIEW

Slowly dissolving gel intended for prevention of biofilm formation in drain and condensate lines.

INTRODUCTION

Condensate lines from chiller and refrigeration units are the ideal breeding ground for some bacteria that are part of our natural environmental microflora and do not normally cause us any problems. These bacteria can arise from the water in the drain or be introduced from the air through the recirculation fans of the cooling system. Organic material from food residues along with the right amount of heat, oxygen and moisture encourage these bacteria to grow and form a biofilm around pipework and drains. However, in many circumstances the repeated hot and cold cycles, periods of starvation and low water activity are very stressful on these bacteria and they have evolved a mechanism to deal with this. They produce a thick, slimy, protective coat composed of 'extracellular polysaccharide' (or 'EPS'). The result of this is that normally invisible bacteria become very visible and their EPS coats form one single mass of gel. This gel can harden and quickly block the drain lines causing flooding, cooling failure, closure of isles in retail with loss of profits, foul smells, and high reactive plumbing costs.

TECHNICAL DESCRIPTION

Chillguard is a dual-action biocidal product formulated as a slow release gel. Intended for painting on to the surface of drip pans and drainage gulley's of systems designed for handling low flow drainage of waste water and condensates. The product is versatile for use in a variety of systems but especially those that experience wet and dry cycles that encourage EPS formation.

The formulation combines an amphoteric surfactant with biocidal properties with a bigaunide. Both materials have for many years been in common use in a range of hygiene products and applications.

ChillGuard can be used as a single treatment solution for EPS control in drainage systems or in combination with RBC BioTab and Cleaner Disinfectant provide a complete solution for chiller and refrigeration EPS problems.

FEATURES & BENEFITS

Features	Benefits
Thick gel formulation	Slow release of actives
Odourless formulation	Control of EPS formation; reduces blockages
No chlorine	Reduce isle closure and loss of profit
Convenient pack size	Controls foul odour
Easy to use	Reduces frequency of manual cleaning
Long lasting formulation	Reduces cost reactive maintenance
Compatible with all other cleaners	Active for up to 6 months

APPLICATION AREAS

- Condensate drain lines
- Chiller and refrigeration drip pans
- Air conditioning drip trays
- Drainage gulleys

Compatible with all plumbing materials and surfaces including HDPE, polycarbonates, copper, stainless steel, non-vulcanized rubber seals, adhesives and sealants.

INSTRUCTIONS FOR USE

It is advisable to pre-clean the surface using OilOff. This will remove any grease residues and improve bonding of Chillguard.

Pour gel onto pre-cleaned and degreased surface of a drainage gulley. Spread over the entire surface with a suitable bush. The product will not air dry.

As condensate runs over the gel it is activated and slowly releases the actives into the drainage system will keep the drain free from EPS and other slime. When the gel layer has almost completely dissolved, repaint the surface. Frequency of re-application will depend upon the size and design of the chiller/refrigeration unit, type of food, atmospheric humidity, temperature, historical performance characteristics and timing of service cycles

Always use biocides safely. Always read the label and product information before use. Refer to the Safety Data Sheet for detailed handling/storage instructions.

PACKAGING

12x1L bottles/case

The information provided in this Technical Data Sheet is accurate at the date of issue and should be used for indicative purposes only. Please refer to your Company Representative for specific User instructions as to how these relate to your usage requirements. Please note that Rumexo Ltd is not liable for claims, damages, costs or expenses of any kind arising from the mishandling of the product or changes that might occur during the handling, storage and application conditions provided by any third party who does not follow the minimum requirements defined in the SDS. Please refer to the SDS for further information regarding the handling, storage and application procedures for the product.